

Eco SERVICE

CHEMICAL PRODUCTS



METAL TREATMENT



1. Surface preparation with technical detergents and degreasers.

They remove dirt, grease, and contaminants.



2. Removal and treatment with rust removers, strippers and rust activators.

They eliminate oxides or are used to achieve controlled and decorative oxidative effects.



3. Special and aesthetic protection through transparent protectors.

They stabilize the Corten patina and preserve its appearance.



4. Corrosion protection through the use of anti-rust products.

Galvanizing agents, rust converters, primers and protective paints.

Proper substrate preparation:

Preliminary phase

On new or sanded surfaces.



Restoration phase

On surfaces already showing signs of corrosion.



Technical introduction to the range of products for the protection and treatment of metals

Metal corrosion causes structural and functional deterioration of facilities and infrastructure.

Oxidation, galvanic corrosion, and chemical attack compromise the mechanical integrity, reliability, and appearance of products. The catalogue offers solutions for surface protection and treatment.

- Detergents and degreasers for substrate preparation
- Deoxidisers and strippers for the removal of rust
- Oxide activators for controlled oxidative effects
- Transparent protectors for Corten effect
- Anti-corrosion protectants: galvanizers, converters, primers and paints

All systems are designed to guarantee effective and long-lasting corrosion protection on different types of metal: iron, carbon steel, galvanized steel, zinc, aluminum, brass and metal alloys.

Technical approach to corrosion protection

Metal protection requires an integrated approach that takes into account:

- The nature of the metal support
- The extent of corrosion present
- The environmental conditions of use
- The planned treatment and finishing cycle

The proposed solutions are designed to act specifically both in the preventive phase, on new or sandblasted surfaces, and in the restoration phase, on surfaces already affected by corrosion. Proper substrate preparation plays a fundamental role and is achieved using specific detergents and rust removers, essential to ensure the adhesion and durability of subsequent protective coatings.

The detergents and rust removers in the range allow you to:



Eliminate organic pollution and industrial waste.



Remove surface oxidation and inconsistent patinas.



Improve the wettability and adhesion of subsequent products.



Properly prepare the substrate for coating and protective treatment

Typical applications:



Light and heavy metal carpentry.



Industrial maintenance.



Exposed metal structures



Automotive, agricultural and nautical sectors.

Detergents, rust removers and surface preparation

The quality of the anti-corrosion cycle depends largely on the initial preparation of the metal. Oils, greases, machining residues, oxides, and impurities significantly reduce the adhesion of primers and varnishes, compromising the durability of the treatment.

The detergents and rust removers in the range allow you to:

- Eliminate organic pollution and industrial waste
- Remove surface oxidation and inconsistent patinas
- Improve the wettability and adhesion of subsequent products
- Properly prepare the substrate for coating and protective treatment

Rust converters and galvanizing treatments

Rust converters chemically react with iron oxides, transforming them into stable, insoluble compounds suitable for use as a passivation layer and as a base for subsequent painting cycles.

Cold galvanizing products with high zinc content guarantee active cathodic protection, counteracting corrosion even in the presence of surface damage to the protective film.

Typical applications:

- Light and heavy metalwork
- Industrial maintenance
- Exposed metal structures
- Automotive, agricultural and nautical sectors

Phase 1 Controlled oxidation

Using rust
activators.

Phase 2 Stabilization and protection

Using transparent
protectors.



Reduction in
rust flaking.



Reduction of
pigment and
residue release.



Reduction of the
uncontrolled
progression of
corrosion.



High adhesion to the substrate



Protection of the metal from external agents



Compatibility with subsequent topcoats

Rust activators and protectors for the Corten effect

For architectural and decorative needs, the range also includes products designed to achieve the Corten effect, which is obtained through the controlled oxidation of the metal surface.

Rust activators accelerate and standardize the oxidation process, achieving a characteristic and reproducible aesthetic patina.

Subsequently, the transparent protectors help stabilize the finish, reducing:

- The release of rust
- The release of pigments and residues
- The uncontrolled progression of corrosion

These solutions allow you to combine aesthetics and durability, maintaining the characteristic appearance of oxidized metal over time.

Primers for metals and anchoring systems

Anti-corrosion primers play a fundamental role in the protection cycle, ensuring:

- High adhesion to the substrate
- Protection of the metal from external agents
- Compatibility with subsequent topcoats

Specific formulations are available for ferrous, galvanized and non-ferrous surfaces, suitable for application by brush, roller or spray.



Resistance to corrosion and UV rays



Long-term film stability



Easy to apply and maintain



Uniform and professional finishes

Protective paints and finishes

Protective paints complete the anti-corrosion cycle, guaranteeing resistance to atmospheric, chemical, and mechanical agents.

The formulations are designed to maintain protective performance and aesthetic appearance over time, even under severe environmental conditions.

Main features:

- Resistance to corrosion and UV rays
- Long-term film stability
- Easy to apply and maintain
- Uniform and professional finishes

Quality control and technical support

All products are developed in accordance with rigorous quality criteria and undergo internal controls to ensure consistent performance and long-lasting reliability. Each product comes with a technical data sheet, application instructions, and recommended cycles, essential tools for both the end user and the sales network.

The catalogue is a clear and well-structured operational guide, designed to help agents and retailers:

- Quickly identify the right product based on the metal and the application
- Recommend complete and appropriate anti-corrosion treatments
- Explain complex technical concepts to end customers in simple terms

Technical support is an integral part of our service and guides customers from product selection through to the correct on-site application.



BOX – RECOMMENDED CYCLE FOR THE TREATMENT AND PROTECTION OF METALS

To ensure adhesion, durability and effective corrosion protection, it is recommended to follow a complete 4-phase cycle:

01

Cleaning

Alcor | Sgrass | Pulinox | Polarfoam

They eliminate oils, grease, industrial waste and contaminants.

02

Pretreatment

Pulimetal

It removes surface oxides and patinas, improving substrate preparation.

03

Active protection

Armax | Metal Protect | Transparent Antirust | Konverter | Renox | Galvanizers| Antirust Primer

They stabilize corrosion, create anchoring and provide basic corrosion protection.

04

Finish

Colored antirust | Antique | Catramix | Plastic Spray | Protex

They ensure long-lasting resistance to atmospheric, chemical, and mechanical agents.



BOX – CORTEN EFFECT CYCLE ON IRON

Eco Service professional system in 3 phases to achieve a Corten effect on iron surfaces through substrate preparation, controlled oxidation and final protection.

01 - PREPARATION OF THE SUPPORT

PULIMETAL – Metal Stripper

- Remove paint, scale, loose oxides, grease and manufacturing residues.
- Sand or brush until the metal surface is clean and uniform.
- Apply PULIMETAL evenly to the surface.
- Leave to act for a period appropriate to the condition of the substrate.
- Thoroughly remove the product and any residues.
- Rinse if necessary and dry completely.

The goal: a clean, uniform surface ready for subsequent oxidation.

02 - CREATION OF THE CORTEN EFFECT

OXEN – Corten-effect rust activator

- Apply OXEN to the surface previously treated with PULIMETAL.
- Apply evenly using a brush, spray or sponge.
- Leave to react until oxidation appears.
- Repeat the application until the desired effect is achieved.
- We recommend applying 2–4 light coats.
- Allow the oxidation to develop fully before applying the final protective coat.

The goal: to achieve a natural, textured finish with the characteristic shades of Corten steel.

03 - STABILIZATION AND FINAL PROTECTION

METAL PROTECT / ANTIRUST TRANSPARENT SPRAY - Transparent antioxidant protector

- Check that the oxidation achieved with OXEN is fully developed and dry.
- Remove any loose rust with a soft brush or a gentle air blast.
- Apply METAL PROTECT/ANTIRUST TRANSPARENT SPRAY in 1–2 light coats.
- Spread evenly, avoiding excess.
- Allow to dry between coats.

The goal: to halt active oxidation, reduce dusting and protect the finish without altering its appearance.

APPLICATION CONDITIONS

- Apply on dry, clean surfaces free of impurities.
- Recommended temperature: +10 °C / +30 °C.
- Avoid rain, condensation, high humidity and overheated surfaces.
- Always perform a preliminary test on a sample.

WARNINGS

- Do not apply to wet or contaminated surfaces.
- Do not apply METAL PROTECT before the oxidation has fully matured.
- For outdoor applications, periodically check the condition of the finish.

Correct sequence:

- PULIMETAL → prepares the surface
- OXEN → creates the Corten effect
- METAL PROTECT o ANTIRUST SPRAY → stabilizes and protects

Pulimetal
Metal stripper



Oxen
Corten-effect rust activator



Metal protect/Antirust spray
Transparent anti-rust protective coating



Product Index

Detergents and Rust Removers

S10	ALCOR	page 8
SG610	SGRASS SPRAY	page 9
PU510	PULINOX TRIGGER	page 10
PO110	POLARFOAM SPRAY	page 11
PU750	PULIMETAL	page 12

Converters and Galvanizers

KO510	KONVERTER	page 17
RE550	RENOX	page 18
AX410	ARMAX	page 14
ZC310	ZINCO CHIARO	page 19
ZB310	ZINCOBRIL SPRAY	page 20
ZS310	ZINCO SCURO	page 21
ZK616	ZINKPROT SPRAY	page 22
AI810	ACCIAIO INOX SPRAY	page 23
AL510	ALLUMINIO SPRAY	page 24
ZO310	ZINCORO SPRAY	page 25

Activators and Protectors

OX550	OXEN	page 13
MP650	METAL PROTECT	page 15
AN010	TRANSPARENT ANTIRUST SPRAY	page 16

Primers and Paints

TP604	PRIMER ANTI-RUST SPRAY	page 26
AN010	ANTIRUST SPRAY	page 27
TP410	ANTIQUÉ SPRAY	page 28
CA110	CATRAMIX	page 29
PL410	PLASTIC SPRAY	page 30
PX310	PROTEX SPRAY	page 31

S10 - ALCOR

Product description

Super concentrated universal degreaser.

Characteristics

- Biodegradable formula.
- Free from hydrocarbon solvents.
- Removes grease, oil, grime, old layers of dirt and tough stains.
- Controlled foaming: easy rinsing and no residue.
- Also suitable for use with floor cleaning machines and pressure washers.

Applications and how to use

Suitable for a variety of applications, it can be applied to most water-washable surfaces: plastic, metal, resin, painted surfaces, tiles, porcelain, enameled surfaces, wall coverings, etc. Ideal for quickly removing grease and stubborn dirt from washable surfaces. Depending on the type and amount of dirt, dilute the product 1:1 to 1:10. Apply the solution by spraying or with a cloth, brush, or sponge. After application, wait about 1 minute; if necessary, scrub. Then rinse thoroughly with water. For use in cleaning machines (pressure washers, floor cleaners, etc.), dilute 1:10 to 1:30 and follow the manufacturer's instructions. Specific treatment for ferrous materials (steel/cast iron) contaminated with grease and oil: pre -dilute 1:3–1:8 depending on the degree of contamination. Apply by spray or dip, leave to act for 1–3 minutes, and brush if necessary. Rinse with water. To prepare for painting or subsequent treatment, perform a thorough final rinse and dry the surface completely to avoid surface oxidation.

Chemical/Physical Specifications

PARAMETER	DESCRIPTION
Basic components	Anionic and non-ionic surfactants
Appearance	Liquid clear
Odor	Characteristic
Density	1,06 ± 0,02 g/ml at 20 °C
pH	12,7 ± 0,3
Biodegradability	> 90%

Packaging

Description	Format	Color	Product Code	EAN Code
Bottle	1 Lt	Fluorescent yellow	60511/01	8 027354 605110
Tank	5 Lt	Fluorescent yellow	60511/05	8 027354 605158



SG610 - SGRASS SPRAY

Product description

Industrial degreaser.

Characteristics

- High degreasing action.
- Rapid evaporation.
- Leaves no residue.
- High performance.
- Ready to use.

Applications and how to use

A highly solvent product, ideal for quickly removing grease, oil, lubricants, carbon residue, and stubborn dirt from metal surfaces and mechanical components. Its fast-evaporating formula leaves no residue. Suitable for cleaning and degreasing gears, bearings, chains, transmission components, engine parts, tools, molds, and industrial machinery. Suitable for preparing surfaces before gluing, sealing, protective treatments, or painting. Suitable for routine and extraordinary maintenance on production systems, mechanical panels, workshop equipment, and metal components in general. Suitable for industrial maintenance, automotive, metalwork, plant engineering, naval, and artisanal sectors. Spray onto the surface to be treated from a distance of 15–25 cm, let sit for a few seconds, and remove dirt with a cloth or compressed air. Repeat if necessary. Use in well-ventilated areas.

Chemical/Physical Specifications

PARAMETER	DESCRIPTION
Basic components	Mixture composed of aggressive, non-toxic detergents and solvents
Propellant	Odorless and non-toxic denatured hydrocarbons
Odor	Characteristic
Flammability	Flammable
CFCs harmful to the ozone layer	None
Degreasing power	High

Packaging

Description	Format	Color	Product Code	EAN Code
Spray can	500 ml	Transparent	86610/05	8 027354 866108



PU510 - PULINOX

Product description

Stainless steel cleaner.

Characteristics

- Evaporates quickly without leaving residue.
- Fragrance - free addition.
- Fast and effective action.
- It does not require rinsing.
- Sanitizes without leaving halos.

Applications and how to use

Ready-to-use professional formula with a fast-evaporating alcohol base, ideal for daily cleaning and sanitizing metal surfaces. Ideal for cleaning and sanitizing stainless steel and chrome surfaces. Leaves a light protective film that helps reduce the formation of future streaks. Free from abrasives, it protects treated surfaces from stains, dust, fingerprints, and corrosion. Specifically designed for kitchens, refrigerators, professional equipment, elevator doors, bar counters, and the food industry. Ensure the surface is clean beforehand. Apply or spray a light coat, then remove excess with a dry cloth and polish. The product is not classified as a disinfectant or sanitizer.

Chemical/Physical Specifications

PARAMETER	DESCRIPTION
Appearance	Liquid clear
Composition	Mixture of solvents
Specific weight	0,915 g/cm ³
Odor	Mild, characteristic of alcohols
Solubility in water	Completely miscible
pH	3,6
Biodegradability	> 90%

Packaging

Description	Format	Color	Product Code	EAN code
Trigger Bottle	750 ml	Colorless	62510/75	8 027354 625750



PO110 - POLARFOAM SPRAY

Product description

Foaming cleaner for stainless steel.

Characteristics

- Ready to use.
- Scented.
- It leaves no streaks.
- Neutral pH.
- No rinsing required.

Applications and how to use

Specific product for the professional cleaning of stainless steel. Ideal for cleaning, polishing, and sanitizing chrome-plated and satin-finish stainless steel surfaces without rinsing. It forms a thin protective layer that reduces streaks, fingerprints, and dust buildup. Suitable for kitchens, refrigerators, professional equipment, and washable surfaces such as plastic, wood, glass, metal, ceramic, and aluminum. The special alcohol-based formula with a foaming effect ensures high effectiveness in professional and home applications. Free from abrasives. Directions for use: Shake the can well. Spray from a distance of 15–20 cm, let the foam act for a few minutes, and remove with a disposable paper towel. This product is not classified as a disinfectant or sanitizer.

Chemical/Physical Specifications

PARAMETER	DESCRIPTION
Basic components	Mixture of biodegradable degreasing components
Propellant	Odorless and non-toxic denatured hydrocarbons
Flammability	Flammable
Contains	Non-ionic surfactants
CFCs harmful to the ozone layer	None

Packaging

Description	Format	Color	Product Code	EAN Code
Spray can	400 ml	Colorless	87110/04	8 027354 871102





Eco SERVICE

CHEMICAL PRODUCTS

PU750 - PULIMETAL

Product description

Deoxidizer and descaler for metals.

Characteristics

- Deoxidizes and descales with a single product.
- Quickly removes rust and limescale.
- Suitable for multiple surfaces.
- Restores the original shine.
- High yield even when diluted.

Applications and how to use

Acid-based pickling agent specifically designed for removing oxidation, limescale, and cement residue from metal and ceramic surfaces. It also removes welding residue from ferrous materials and carbon or alloy steel surfaces. Its chemical composition allows for: eliminating slag, oxides, welding spatter, and flux residues, restoring metal surface cleanliness, and preparing the substrate for subsequent processing (painting, galvanizing, protective treatments, or surface finishes). It is suitable for industrial applications, metalwork, mechanical workshops, and structural steelwork. Apply with a brush, by immersion or with a sponge. Use as a Deoxidizer: Protect painted surfaces, remove loose rust, apply the product undiluted, and let it act for 15–30 minutes. Rinse thoroughly, dry, and apply a rust inhibitor. Use as a descaler: use neat or diluted max 1:1. Apply, leave to act for a few minutes, scrub if necessary and rinse with running water.

Chemical/Physical Specifications

PARAMETER	VALUE
Odor	Characteristic
Density (Kg/dm ³)	1,167 ± 0,010
Viscosity at 20°C (cPs)	n.a.
Surfactants biodegradable	> 90%
Yield per liter	15 - 18 m ²

Packaging

Description	Format	Color	Product Code	EAN code
Bottle	750 ml	Colorless	61710/750	8 027354 617755
Tank	5 Lt	Colorless	61750/04	8 027354 617540



OX550 - OXEN

Product description

Corten effect rust activator.

Characteristics

- Rapidly activates the oxidation of ferrous metals.
- Compatible with all raw ferrous substrates.
- Natural and controlled decorative effects.
- Spray, brush or sponge application.
- Ideal for artistic and architectural applications.

Applications and how to use

Liquid chemical activator for the controlled formation of oxidation on ferrous metals and Corten steel. It quickly creates a uniform, natural rust effect on decorative and architectural metalwork. Used in interior design, industrial decoration, set design, and artistic crafts by blacksmiths, decorators, metalworkers, and designers to create antique finishes on iron. Apply the product as is to rough, clean, dry, and degreased surfaces. If necessary, lightly sand the surface. Apply by spray, brush, or sponge depending on the desired effect. Work between 5°C and 35°C, keeping the surface moist. If necessary, apply a second coat and, if necessary, spray with salt water to intensify the effect. Let it react for 24 hours and rinse with water. After use, tools should be cleaned simply with water.

Chemical/Physical Specifications

PARAMETER	VALUE
Appearance	Liquid clear blue
Density (20°C)	1.05 - 1.08 g/ml
Odor	Characteristic
pH	1 - 1.5
Solubility in water	Soluble
Freezing temperature	n.d.
Boiling temperature	n.d.
Yield	From 10 to 15 m ² lt

Packaging

Description	Format	Color	Product Code	EAN code
Bottle	1 Lt	Sky blue	63550/01	8 027354 635018





ECO SERVICE

CHEMICAL PRODUCTS

AX410 - ARMAX SPRAY

Product description

Protective spray for reinforcing bars.

Characteristics

- Contains special corrosion inhibitors.
- High anchoring power.
- Applicable directly to adherent rust.
- High coverage and anti-corrosive power.
- Quick drying – self-cleaning valve.

Applications and how to use

A ready-to-use, single-component product formulated with acrylic resins and specific active corrosion inhibitors, designed to protect steel reinforcement during reinforced concrete repairs. It forms a continuous, compact, and highly adherent protective film on the metal substrate, effectively counteracting oxidation and preventing the onset of new corrosion. Specifically designed to protect exposed reinforcing bars following carbonation or detachment of the concrete cover during maintenance, renovation, and structural restoration of reinforced concrete structures in civil, industrial, and infrastructure projects. It can be used both as a protective treatment during repairs and as a preventative protection for reinforcement prior to subsequent repairs with structural mortars compliant with EN 1504-3. Before application, it is necessary to completely remove the degraded concrete down to sound iron and remove rust, oxides, dust, grease, and loose particles by mechanical brushing or sandblasting until the substrate is clean, solid, and dry. The can should be shaken vigorously for at least one to two minutes before use; apply evenly from a distance of approximately 25–30 cm. Apply two or three coats of product, approximately 30–40 minutes apart, ensuring complete coverage of the metal surface with a continuous, even layer of at least 1–2 mm. The repair mortar should be applied only after at least 8 hours, and in any case, after the anti-corrosion treatment has completely dried.

Chemical/Physical Specifications

PARAMETER	METHOD	U.M.	VALUE
Binder	-	-	Acrylic
Dust-dry	MP016	Min	7 - 10
Dry to the touch	MP016	Min	15 - 25
Deep drying	MP016	Hours	24 - 36
Steam pressure 20°C	Gauge	Bar	5 ± 0.2
Operating pressure	Gauge	Bar	10
Burst pressure	Gauge	Bar	18
LPG flash point	-	°C	< - 50
VOC content	-	g/l	Max 588
Temperature resistance	-	°C	≤ 80
Coverage 400 ml (4 coats)	-	m ²	1 - 1,2

Packaging

Description	Format	Color	Product Code	EAN Code
Spray can	400 ml	Matt blue	91410/001	8 027354 914014



Eco SERVICE

CHEMICAL PRODUCTS

MP650 - METAL PROTECT

Product description

Transparent anti-rust protector.

Characteristics

- High penetrating power and deep stabilization.
- Inhibition of the oxidative process.
- Excellent adhesion to rust and old adherent paint.
- Improves weather resistance.
- Transparent reviving effect.

Applications and how to use

High-performance, transparent rust inhibitor formulated to block and stabilize oxidation processes in iron products. Professional formulation based on vegetable oils and alkyd resins with excellent penetration and rust stabilization. Used in construction, industry, civil maintenance, metalwork, blacksmithing, installation, and restoration. Suitable for railings, gates, shutters, trellises, silos, and metal structures made of steel, zinc, copper, and aluminum. Excellent as a primer for galvanized surfaces. Applied to CORTEN steel, it stops the oxidation process and maintains the natural appearance of rust. It enhances the appearance of the treated item and can be left as a finish. Adding 3–5% synthetic enamel improves flow and weather resistance. The product is also used as a primer for windows and external wooden cladding. Apply as is by brush or spray to dry, clean, and degreased surfaces. If oxidation is severe, apply a second coat. Recoatable after 24-48 hours.

Chemical/Physical Specifications

PARAMETER	U.M.	VALUE
Appearance	-	Clear
Water Content	% p/p	≤1
Density	Kg/L	0.8 - 0.9
Odor	-	Characteristic
Dry residue	%	45
Estimated yield	m ² /L	18 - 20

Packaging

Description	Format	Color	Product Code	EAN code
Bottle	1 Lt	Transparent satin	63650/01	8 027354 636015





Eco SERVICE

CHEMICAL PRODUCTS

AN010 - "TRANSPARENT" ANTIRUST SPRAY

Product description

Transparent protective anti-rust.

Characteristics

- It stops the rusting process and dusting.
- Suitable for use on adherent rust.
- High coverage and protection.
- It keeps the natural appearance of rust unchanged.
- Weather resistant, does not yellow.

Applications and how to use

High-performance spray coating based on zinc phosphate and rust inhibitors with protective, anchoring, and rust-preventing properties. Specifically designed for ferrous materials, steel, and metal structures in general. Ideal for Corten-effect surfaces, it stabilizes oxidation while preserving their original appearance. Apply to clean, dry surfaces. Shake for 1 minute. Apply at a distance of 25–30 cm with light, crisscross strokes. Dust-free in 7–10 minutes; touch-free in 15–25 minutes; full-coverage in 24–36 hours. Recommended minimum thickness: 30 microns (4–8 coats). Suitable for ferrous metals (including Corten effect), primed non-ferrous metals, wood, and ABS/PVC.

Chemical/Physical Specifications

PARAMETER	METHOD	U.M.	VALUE
Glossy finish	MP004	Gloss	88 - 92
Matt finish	MP004	Gloss	2 - 6
Binder	-	-	100% Acrylic
Thickness (4 coats)	ISO2808	Micron	13 - 15
Dust-dry	MP016	Min	7 - 10
Dry to the touch	MP016	Min	15 - 25
Operating pressure	Gauge	Bar	10
VOC	-	g/l	Max 614
Temperature resistance	-	°C	≤ 80
Coverage 400 ml (4 coats)	-	m²	1 - 1,2

Packaging

Description	Format	Color	Product Code	EAN code
Spray can	400 ml	Transparent Gloss	72010/008	8027354720080
Spray can	400 ml	Transparent Matt	72010/009	8027354720097





Eco SERVICE

CHEMICAL PRODUCTS

KO510 - KONVERTER

Product description

Rust converter.

Characteristics

- High anti-corrosion power and prevents rust formation.
- It transforms rust into a stable, adherent compound.
- Excellent primer, overpaintable.
- Quick drying.
- Free from Lead, Cadmium and Chromium.

Applications and how to use

Formulated to transform adherent rust into a stable and inert compound, creating a protective base ready for subsequent painting. Suitable for the construction (reinforcement protection), automotive, and industrial sectors for the maintenance of joints, welds, machinery, tanks, pipes, gates, and ferrous metal structures. Apply to dry surfaces free of oil, grease, and loose particles. Remove scale with a brush or abrasive. Apply by brush, roller, or spray at a distance of 25–30 cm. Full reaction time 24–48 hours. Clean tools with Nitro Thinner.

Chemical/Physical Specifications

PARAMETER	LIQUID DESCRIPTION	AEROSOL DESCRIPTION
Physical state	Liquid viscous	Aerosol
Odor	Characteristic	Characteristic
Propellant gas	-	Denatured hydrocarbons. Odorless, non-toxic.
CFCs harmful to the ozone layer	-	None
VOC Content	-	675 g/l
Density (Kg/dm ³)	1.150 ± 0.010	-
Viscosity 20°C (cPs)	347 ± 10	-
Dry film appearance	-	MP004 - Opaque
Thickness (4 coats)	-	ISO 2808 (13 - 15 microns)
Dust-dry	MP016 (20 min)	MP016 (20 min)
Dry to the touch	MP016 (40 min)	MP016 (40 min)
Complete drying	MP016 (24 hours)	MP016 (24 hours)
Steam Pressure 20°C	-	Pressure gauge : 5 ± 0.2 bar
Flash point	-	< - 50°C
Coverage yield	15 m ² /L	400 ml (4 passes) 0.8 - 1 m ²

Packaging

Description	Format	Color	Product Code	EAN Code
Bottle	250 ml	Milky white	61510/250	8 027354 615256
Bottle	750 ml	Milky white	61510/750	8 027354 615751
Tin can	4 Lt	Milky white	61550/04	8 027354 615546
Spray can	400 ml	Amber	86010/04	8 027354 860106

RE550 - RENOX

Product description

Phosphating rust converter.

Characteristics

- Dual action rust converter and pickler.
- High chemical reactivity on iron oxides.
- Easily applicable liquid formulation.
- Miscible with water in all proportions.
- Suitable for maintenance and restoration treatments of metal surfaces.

Applications and how to use

Acid-based liquid rust converter designed to block and transform rust on ferrous metal surfaces. The product chemically reacts with iron oxide, converting it into a stable layer that slows the corrosion process. Contains zinc oxide and can be painted over. It can be used both as a converter treatment and as a pickling agent for rust removal. It is used in the maintenance of metal structures, carpentry, mechanical components, industrial equipment, and metal surfaces exposed to atmospheric agents. Used by maintenance workers, body shops, machine shops, the construction sector, and the metalworking industry. First, remove any larger pieces of rust using sandpaper or a wire brush. Apply the pure converter with a brush or spray, distributing it evenly over the affected surface. Let it react for approximately 3–5 minutes, then rinse or remove any residue. Then apply a second coat of product and let it react until completely dry naturally, approximately 12 to 24 hours. During the first 3–4 hours, protect the surface from rain or water and work preferably in the shade, avoiding direct sunlight.

Chemical/Physical Specifications

PARAMETER	VALUE
Appearance	Clear, colorless liquid
Density (20°C)	1.28 - 1.30 g/ml
Odor	Characteristic
pH	1 - 1.5
Solubility in water	Soluble
Yield	15-20 m ² /lt

Packaging

Description	Format	Color	Product Code	EAN code
Bottle	500 ml	Transparent	61550/05	8027354615058





ZC310 - ZINCO CHIARO

Product description

Cold galvanizer (clear).

Characteristics

- High content of pure zinc (98%) for effective protection.
- Single-component, ready to use with brush or spray.
- Excellent rust protection with high corrosion resistance.
- High heat resistance up to 700°C.
- Quick drying, good elasticity and overpaintable.

Applications and how to use

Formulated for corrosion protection and restoration of galvanized and ferrous surfaces. Suitable for metalwork, gates, railings, bolts, welds, pipes, windows, and structures exposed to industrial, rural, or marine environments. Liquid version: use neat or diluted up to 10% with synthetic solvent. Apply to clean, degreased surfaces. Aerosol version: shake before use, apply from about 25 cm; after use, invert and empty the dispenser. Do not apply in rain, fog or strong wind.

Chemical/Physical Specifications

PARAMETER	DESCRIPTION LIQUID	AEROSOL DESCRIPTION
Basic components	Zinc 98% pure	Zinc 98% pure
Physical state	Liquid	Aerosol
Propellant gas	-	Hydrocarbons denatured
CFC	-	None
Covering power	High	High
Heat Resistance	700°C	700°C
Dry film thickness	30 - 40 µm	20 - 40 µm
Drying	Quick	Quick
Elasticity	Good	Good
Resistance to abrasion	Very good	Very good
Yield	4 - 5 m ² /kg	120 ml/m ²
Odor	Characteristic	Characteristic
Application	Brush/Spray	Spray 25 cm

Packaging

Description	Format	Color	Product Code	EAN code
Tin can	1 kg	Clear Zinc	81350/75C	8027354813751
Tin can	4 kg	Clear Zinc	81350/04C	8027354813546
Spray can	400 ml	Clear Zinc	81310/04	8027354813102



ECO SERVICE

CHEMICAL PRODUCTS

ZB310 - ZINCOBRIL SPRAY

Product description

Cold galvanizer (bright).

Characteristics

- High content of pure zinc (98%) with active electrochemical protection.
- Can with non-drip dispenser and self-cleaning valve.
- Ready-to-use, quick-drying and non-drip.
- Heat and salt spray resistance.
- Forms an elastic, overpaintable, anti-corrosion film.

Applications and how to use

Formulated with a high content of pure, bright zinc in a synthetic carrier. Specifically designed for restoring galvanization on metalwork, steel structures, industrial plants, gates, fences, bolts, and welds. Provides active cathodic protection against corrosion, oxidation, and atmospheric agents. Used in industrial, construction, metal maintenance, carpentry, shipbuilding, and automotive sectors. Suitable for blacksmiths, window and door installers, maintenance technicians, and mechanical workshops. Shake before use. Apply to clean, degreased surfaces from about 25 cm away. After use, invert the can and spray for a few seconds to clean the valve.

Chemical/Physical Specifications

PARAMETER	VALUE
Physical state	Aerosol
Propellant gas	Denatured hydrocarbons, odorless, non-toxic
Basic components	Zinc 98% pure
Dry film thickness	20/40 microns
Drying	Quick
Elasticity	Good
Resistance to abrasion	Very good
Cross-section	GT0/GT1
Resistance to oxidation	Excellent
Coverage yield	120 ml/m ²

Packaging

Description	Format	Color	Product Code	EAN code
Spray can	400 ml	Bright Zinc	81310/04B	8 027354 813119





ZS310 - ZINCO SCURO

Product description

Cold galvanizer (dark).

Characteristics

- Pure zinc (98%) with active cathodic protection.
- Anti-rust and anti-corrosion protection (>500 hours salt spray).
- Heat resistance up to 700°C.
- Quick drying, non-drip, overpaintable.
- Available in single-component liquid version and spray can with self-cleaning valve.

Applications and how to use

Formulated for corrosion protection and restoration of galvanized and ferrous surfaces. Suitable for metalwork, gates, railings, bolts, welds, pipes, windows, and structures exposed to industrial, rural, or marine environments. Liquid version: use neat or diluted up to 10% with synthetic solvent. Apply to clean, degreased surfaces. Aerosol version: shake before use, apply from about 25 cm; after use, invert and empty the dispenser. Do not apply in rain, fog or strong wind.

Chemical/Physical Specifications

PARAMETER	LIQUID DESCRIPTION	AEROSOL DESCRIPTION
Basic components	Zinc 98% pure	Zinc 98% pure
Physical state	Liquid	Aerosol
Dry film thickness	40 - 50 microns	30 - 60 µm
Propellant gas	-	Hydrocarbons denatured. Odorless, non-toxic.
CFCs harmful to the ozone layer	-	None
Heat resistance	Up to 700°C	Up to 700°C
Drying	Quick	Quick
Covering power	High	High
Elasticity	Good	Good
Conductivity electric	Good	Good
Resistance to abrasion	Very good	Very good
Cross-section	GTO - DIN 53151 / ISO 2409	GTO - DIN 53151 / ISO 2409
Salt Spray Test	> 500 HOURS - DIN 50021 / ISO 9227	> 500 HOURS - DIN 50021 / ISO 9227
Coverage yield	4 - 5 m ² /kg	≈150 ml/m ²

Packaging

Description	Format	Color	Product Code	EAN code
Tin can	1 kg	Dark Zinc	81350/75	8 027354 813768
Tin can	4 kg	Dark Zinc	81350/04	8 027354 813553
Spray can	400 ml	Dark Zinc	81310/04S	8 027354 813133

ZK616 - ZINKPROT SPRAY

Product description

Protective zinc coating (bright).

Characteristics

- Excellent resistance to atmospheric agents and industrial environments.
- Quick drying and ready to be painted over.
- Fair anticorrosive power.
- Adheres to various ferrous surfaces.
- Can with a non-drip dispenser and self-cleaning valve.

Applications and how to use

Ideal for protecting iron surfaces. Restores and evens out the appearance of galvanization, ensuring a shiny, durable finish. Suitable for protecting and repairing galvanized metal structures such as gates, fences, pipes, tanks, metalwork, welds, industrial doors, prefabricated structures, and components exposed to the outdoors. Used by installers, industrial maintenance workers, metalworkers, and construction workers. Ensure the surface is dry, clean, and free of oil, grease, and dust. Shake the can vigorously for 1–2 minutes. Apply at a distance of 20–30 cm, holding the can vertical. Use light, crisscross strokes (first vertically, then horizontally), shaking occasionally during use. Drying time: dust-free 7–10 minutes, touch-dry 15–20 minutes, thorough 24–36 hours.

Chemical/Physical Specifications

PARAMETER	METHOD	U.M.	VALUE
Appearance	MP 004	Gloss	Bright metallic
Type of binder	-	-	100% Pure Acrylic
Dust-dry	MP 016	Min	7 - 10
Dry to the touch	MP 016	Min	15 - 20
Deep drying	MP 016	Hours	24 - 36
Propellant	-	-	Butane - Isobutane - Propane
Dispensing system	-	-	Self-cleaning valve
Shelf life	-	-	Min. 60 months (10 - 25°C)
VOC	-	g/l	642
Heavy metals	-	-	None
CFC	-	-	None
Coverage 400 ml (4 coats)	-	m ²	1 - 1,2

Packaging

Description	Format	Color	Product Code	EAN code
Spray can	400 ml	Bright Zinc	90610/616P	8 027354 906163

AI810 - ACCIAIO INOX

Product description

Cold galvanizing spray “Stainless steel”.

Characteristics

- High heat resistance.
- High content of passivating agents/corrosion inhibitors for stainless steel surfaces.
- Adhesion and compatibility with stainless steel.
- Quick drying without dripping.
- Excellent as an anchoring base.

Applications and how to use

Fast-drying metallic film protective spray for the anti-corrosion protection of stainless steel surfaces. Suitable for maintenance, post-welding restoration, mechanical processing, and treatment of critical areas. Directions for use: Shake can; apply to degreased, dry, and rust-free surfaces; spray from approximately 25 cm using a continuous, even motion; for optimal performance, ensure a dry film thickness of $\geq 50 \mu\text{m}$; wait until completely dry between coats; then invert can and spray for a few seconds to prevent clogging of the nozzle.

Chemical/Physical Specifications

PARAMETER	DESCRIPTION
Basic components	Highly pure stainless steel in 98% pure synthetic medium
Propellant	Hydrocarbons denatured odorless
Flammability	Flammable
Solvent	Chlorides and carbonyls
CFCs harmful to the ozone layer	None
Covering power	High
Dry film thickness	25-30 microns
Drying	Quick
Elasticity	Good
Adherence	Good on bare and galvanized metal
Salt spray test	(DIN 50021 - DIN 53167 - ISO 9227) ≥ 200 hours
Weather resistance	Excellent
Coverage yield	Approximately 120 ml/m ²

Packaging

Description	Format	Color	Product Code	EAN Code
Spray can	400 ml	Stainless steel	81810/04	8 027354 818107



AL510 – ALLUMINIO SPRAY

Product description

Cold galvanizer “Aluminium”.

Characteristics

- Spray can with anti-drip dispenser button and self-cleaning valve.
- Single component, ready to use.
- Excellent rust protection.
- High resistance to heat and atmospheric agents.
- Overpaintable elastic film.

Applications and how to use

Formulated to provide professional anti-corrosion protection and a highly resistant technical finish. Suitable for aluminum and ferrous surfaces. Contains a high content of ultra-pure aluminum (98%), formulated to provide professional anti-corrosion protection and a highly resistant technical finish. Suitable for industrial maintenance workers, installers, blacksmiths, and metalworking companies. Ideal for work on metal structures, light and heavy carpentry, gates, fixtures, gutters, tanks, industrial plants, and components exposed to aggressive outdoor environments. Clean and degrease the surface thoroughly. Shake vigorously for at least 2 minutes. Apply from a distance of approximately 20–25 cm, using crisscross strokes until a minimum dry film thickness of 50 µm is achieved. Allow to dry completely between coats. After use, invert the can and spray for a few seconds to clean the valve.

Chemical/Physical Specifications

PARAMETER	DESCRIPTION
Basic Components	98% pure aluminum in a synthetic carrier
Propellant	Odorless denatured hydrocarbons
Flammability	Flammable
CFCs harmful to the ozone layer	None
Covering power	High
Dry film thickness	15 - 20 microns
Drying	Quick
Elasticity	Good
Adherence	Good on bare and galvanized metal
Weather resistance	Excellent
Coverage yield	Approximately 120 ml/m ²

Packaging

Description	Format	Color	Product Code	EAN code
Spray can	400 ml	Aluminium	82510/04	8 027354 825105





ECO SERVICE

CHEMICAL PRODUCTS

Z0310 - ZINCORO SPRAY

Product description

Cold galvanizer (gold).

Characteristics

- High content of pure zinc.
- Excellent rust protection and blocking of corrosion processes.
- High resistance to heat and salt spray.
- Quick drying, non-drip, can be painted over.
- Cans with a non-drip dispenser and self-cleaning valve.

Applications and how to use

Formulated for the anti-corrosion protection of ferrous metal surfaces and for aesthetic and protective restoration of metal components. Restores damaged original galvanization, creating a durable and long-lasting protective coating. Suitable for protecting and restoring metal structures, light and heavy carpentry, fences, gates, bolts, welds, pipes, gratings, tanks, and mechanical parts exposed to atmospheric agents or aggressive industrial environments. Used by industrial maintenance workers, machine shops, installers, blacksmiths, body shops, and the construction industry. Also specifically designed for restoring brass materials such as handles, knobs, plates, decorative plaques, taps, nautical components, hardware, musical instruments, and ornamental details subject to surface oxidation. Ideal for evenly coloring worn or abraded surfaces before final protection. Shake the can vigorously before use. Apply to clean, dry, and degreased surfaces from a distance of about 25 cm. Apply multiple light coats if necessary. After use, invert the can and spray for a few seconds to clean the valve.

Chemical/Physical Specifications

PARAMETER	VALUE
Physical state	Aerosol
Propellant gas	Denatured hydrocarbons, odorless, non-toxic
CFCs harmful to the ozone layer	None
Odor	Caratteristico
Basic components	Pure gold-colored zinc in acrylic vehicles
Covering power	High
Dry film thickness	15 - 20 microns
Drying	Quick
Elasticity	Good
Coverage yield	120 ml/m ²

Packaging

Description	Format	Color	Product Code	EAN code
Spray can	400 ml	Gold	81310/040	8 027354 813126

TP604 - PRIMER ANTI-RUST SPRAY

Product description

Anti-rust primer.

Characteristics

- Contains zinc phosphate with high anti-corrosion power.
- Quick drying and high coverage
- Can be painted over and does not yellow over time.
- Self-cleaning valve for professional use.
- Excellent weather resistance for indoor and outdoor use.

Applications and how to use

Formulated for the anti-corrosion protection of metal surfaces. It ensures high adhesion even on stubborn rust, excellent coverage, quick drying, and high weather resistance. Ideal as a protective primer before a decorative or protective finish. Product recommended for protecting ferrous surfaces such as gates, railings, grilles, shutters, light carpentry, frames, pipes, machinery, agricultural and industrial equipment. Suitable as an anchoring primer on galvanized materials before painting to facilitate adhesion. Intended for construction and industrial professionals, maintenance workers, body shops, blacksmiths, installers, and advanced hobbyists requiring a high-performance anti-corrosion primer. Shake for 1–2 minutes after the start of the clattering sound. Spray 25–30 cm from the surface, holding the can vertically. Apply light, crisscrossing strokes. The surface must be dry, clean, and free of oil, grease, and dust.

Chemical/Physical Specifications

PARAMETER	METHOD	U.M.	VALUE
Matt Appearance	MP004	Gloss	10 - 20
Binder Type	-	-	100% Pure Acrylic
Recommended coats	MP012	Nr.	4 - 6
Thickness (4 coats)	ISO2808	Micron	13 - 15
Dust-dry	MP016	Min	7 - 10
Dry to the touch	MP016	Min	15 - 25
Deep drying	MP016	Hours	24 - 36
Steam pressure at 20°C	Gauge	Bar	5 ± 0,2
Operating pressure	Gauge	Bar	10
Burst pressure	Gauge	Bar	18
VOC	-	g/l	Max 588
Temperature Resistance	-	°C	80 - 90
Coverage 400 ml (4 coats)	-	m ²	0,8 - 1

Packaging

Description	Format	Color	Product Code	EAN Code
Spray can	400 ml	Grey	90610/604P	8 027354 906040
Spray can	400 ml	Red	90610/608P	8 027354 906088

AN010 - ANTIRUST SPRAY

Product description

Glossy anti-rust enamel.

Characteristics

- Contains zinc phosphate and special rust inhibitors.
- Applicable directly to adherent rust.
- High coverage and anti-corrosive power.
- Quick drying – self-cleaning valve.
- Weather resistant – does not yellow.

Applications and how to use

100% pure, multipurpose acrylic enamel: protective, anti-rust, and anchoring. It blocks rust, protects, and coats rusted objects in a single application. Apply to clean, dry surfaces, removing only loose rust without sanding the entire surface. Suitable for iron, zinc, steel, cast iron, aluminum, wood (with primer), ABS, and PVC. Preliminary testing on sensitive plastics. Shake for 1 minute. Spray from a distance of 25–30 cm using thin, crisscross strokes. Drying: dust dry 7–10 min; touch dry 15–25 min; through dry 24–36 h.

Chemical/Physical Specifications

PARAMETER	METHOD	U.M.	VALUE
Bright appearance	MP004	Gloss	82 - 92
Binder	-	-	100% Pure Acrylic
Recommended coats	MP012	Nr.	8 - 10
Thickness (8 coats)	ISO2808	Micron	30 - 35
Dust-dry	MP016	Min	7 - 10
Dry to the touch	MP016	Min	15 - 25
Deep drying	MP016	Hours	24 - 36
Steam pressure 20°C	Gauge	Bar	5 ± 0,2
Operating pressure	Gauge	Bar	10
Burst pressure	Gauge	Bar	18
LPG flash point	-	°C	< - 50
VOC content	-	g/l	Max 588
Temperature resistance	-	°C	≤ 80
Coverage 400 ml (4 coats)	-	m ²	1 - 1,2

Packaging

Description	Format	Color	Product Code	EAN Code
Spray can	400 ml	Pure white	72010/001	8 027354 720011
Spray can	400 ml	RAL 3020 Traffic Red	72010/002	8 027354 720028
Spray can	400 ml	RAL 5010 Gentian Blue	72010/003	8 027354 720035
Spray can	400 ml	RAL 6005 Moss Green	72010/004	8 027354 720042
Spray can	400 ml	RAL 7001 Pearl Grey	72010/005	8 027354 720059
Spray can	400 ml	RAL 8017 Brown	72010/006	8 027354 720066
Spray can	400 ml	RAL 9005 Black	72010/007	8 027354 720073



Eco SERVICE

CHEMICAL PRODUCTS

TP410 - ANTIQUE

Product description

Protective varnish with an antique effect.

Characteristics

- Contains zinc phosphate, mica oxides and anti-corrosive metal pigments.
- Applicable directly to adherent rust.
- High coverage and excellent rust protection.
- Quick drying, self-cleaning valve, does not yellow.
- Weather-resistant and paintable.

Applications and how to use

Professional 100% pure acrylic spray enamel based on micaceous iron, suitable for interior and exterior applications. It provides a sandblasted, antiqued effect, with high corrosion protection and excellent durability. Ideal for gates, railings, pipes, scaffolding, metal furniture and wrought iron objects. The rust effect color is used to reproduce the corten effect on ferrous materials. Clean, dry surfaces free of loose particles. Remove loose rust with a brush or 400-grit sandpaper. Degrease with non-aggressive solvents. Shake the can for at least 1 minute. Apply at a distance of 25–30 cm using light, crisscross, thin strokes. Ideal application temperature: 20–25°C. For optimal protection, apply at least 8–10 crisscross strokes (≈30 dry microns). Do not apply to polystyrene, polyethylene, or polypropylene.

Chemical/Physical Specifications

PARAMETER	METHOD	U.M.	VALUE
Dry film appearance	MP004	Gloss	8 - 6 Opaque
Binder	-	-	100% Acrylic
Recommended coats	MP012	Nr.	Min 4
Thickness (4 coats)	ISO2808	Micron	15 - 17
Dust-dry	MP016	Min	7 - 10
Dry to the touch	MP016	Min	15 - 25
Complete drying	MP016	Hours	24 - 48
Steam pressure 20°C	Gauge	Bar	5 ± 0,2
Operating pressure	Gauge	Bar	10
Burst pressure	Gauge	Bar	18
COV/VOC	-	g/l	Max 612
Temperature resistance	-	°C	80 - 90
Coverage 400 ml (4 coats)	-	m ²	1 - 1,5

Packaging

Description	Format	Color	Product Code	EAN Code
Spray can	400 ml	Light grey	90410/401P	8 027354 904015
Spray can	400 ml	Forge Grey	90410/402P	8 027354 904022
Spray can	400 ml	Black	90410/403P	8 027354 904039
Spray can	400 ml	Grey	90410/406P	8 027354 904060
Spray can	400 ml	Rust Effect	90610/618P	8 027354 906187



Eco SERVICE

CHEMICAL PRODUCTS

CA110 - CATRAMIX

Product description

Protective bituminous paint.

Characteristics

- High anchoring properties and strong adhesion to metals.
- Excellent dustproof, waterproof and elastic characteristics.
- High resistance to abrasion, impacts, atmospheric agents.
- Corrosion protection and saturation of concrete pores.
- Good resistance to weak acids and sound insulation.

Applications and how to use

Formulated for protecting, waterproofing, and saturating metal and concrete surfaces. Ideal for roofs, terraces, tiles, gutters, sheet metal, tanks, scaffolding, flashing, and iron, wood, and concrete structures. Liquid version: Apply by spray, brush, or scrubber on clean, dry surfaces (dilutable with nitro thinner). Spray version: Shake well and apply from 25–30 cm; after use, invert and empty the valve. Avoid extreme temperatures and overheated surfaces.

Chemical/Physical Specifications

PARAMETER	LIQUID DESCRIPTION	AEROSOL DESCRIPTION
Basic components	Bitumen	Bitumen, solvent and propellant
Physical state	Liquid viscous	Aerosol
Odor	Characteristic	Of solvent
Propellant gas	-	Hydrocarbons denatured. Odorless, non-toxic
CFCs harmful to the ozone layer	-	None
VOC content	-	Approx. 0,2819 kg/l
Salt spray (DIN 50021)	-	1000 h (400 µ); 480 h (200 µ)
Density	0,95 - 1,16 Kg/l	-
Dust-dry	30 min ± 10	1,5 h; complete 2,5 h
Viscosity (TF4 20°C)	107 sec ± 20	-
Boiling point	55 - 180°C	-
Flash point	21 °C	-
Overpaintable	Yes	No
Thermal resistance	- 25 °C / + 80 °C	- 25 °C / + 80 °C
Temperature of application	+ 5 °C / + 30 °C	+ 5 °C / + 30 °C
Drying	-	20°C - 65% RH
Coverage yield	5 - 6 m²/L	500 ml (4 passes) 0,5 - 1 m²

Packaging

Description	Format	Color	Product Code	EAN Code
Bottle	750 ml	Black	61110/750	8 027354 611753
Tin can	5 Lt	Black	61150/05	8 027354 611555
Spray can	500 ml	Black	86810/05	8 027354 868102

PL410 - PLASTIC SPRAY

Product description

Protective plasticizing paint.

Characteristics

- Quick drying.
- Overpaintable.
- Self-cleaning valve.
- Excellent durability indoors and outdoors.
- It does not yellow over time.

Applications and how to use

Transparent, invisible, protective spray plasticizer for interior and exterior applications. It forms an elastic, resistant, and long-lasting film, protecting surfaces from deterioration and atmospheric agents. Suitable for: protecting brass, iron, and steel objects from oxidation; protecting documents, photographs, and books from humidity; and waterproofing wood, plastic, cork, and concrete. When using to protect electronic boards and circuits, preliminary testing is recommended to verify compatibility and performance for the specific application. The product contains no metal elements and is not electrically conductive. Apply light, crisscross strokes. The surface must be dry, clean, and free of grease. Use the can at 20-25°C. Shake for 1-2 minutes after feeling the beads inside. Spray from a distance of 25-30 cm, holding the can vertically.

Chemical/Physical Specifications

PARAMETER	METHOD	U.M.	VALUE
Appearance	MP004	Gloss	82 - 92
Binder type	-	-	100% Pure acrylic
Thickness (4 coats)	ISO2808	Micron	13 - 15
Dust-dry	MP016	Min	7 - 10
Dry to the touch	MP016	Min	15 - 25
Deep drying	MP016	Hours	24 - 36
Steam pressure 20 °C	Gauge	Bar	5 ± 0,2
Operating pressure	Gauge	Bar	10
Burst pressure	Gauge	Bar	18
VOC	-	g/l	Max 620
Propellant	-	-	Butane - Isobutane - Propane
Coverage 400 ml (4 coats)	-	m ²	1,2 - 1,5

Packaging

Description	Format	Color	Product Code	EAN Code
Spray can	400 ml	Transparent	86410/04	8 027354 864104

PX310 - PROTEX SPRAY

Product description

Removable protector.

Characteristics

- Resistant to UV rays, atmospheric agents, oils and common detergents.
- Protects non-absorbent surfaces without damage.
- Easy removal without residue.
- Quick drying and high elasticity.
- Overpaintable with solvent-based spray paints.

Applications and how to use

Removable, colored, elastic film for the temporary protection of poorly absorbent surfaces. Forms a uniform, flexible film that protects against atmospheric agents, impacts, abrasions, oils, greases, and oxidation without altering the substrate. Suitable for iron, aluminum, PVC, glass, steel, and metal surfaces in general. Suitable for industrial, construction, automotive, and technical maintenance sectors. Suitable for body shops, workshops, metalworking companies, window and door manufacturers, installers, construction companies, and maintenance personnel. Ideal for transport, assembly, and storage. Use at 20–25°C. Shake the can and spray from a distance of 18–20 cm in crisscross strokes. Apply 5–6 coats, waiting 10 minutes between coats. Peelable after 2–3 hours. Completely dry in 24–36 hours. Do not apply below 15°C or in high humidity.

Chemical/Physical Specifications

PARAMETER	DESCRIPTION
Physical state	Aerosol
Propellant gas	Odorless and non-toxic denatured hydrocarbons
Flammability	Yes
CFCs harmful to the ozone layer	None
Basic components	Resins specials
Temperature resistance	80 °C - 100 °C
Removal	Acetone or nitro thinner
Dry to the touch	10 - 15 minutes
Coverage 400 ml (5 - 6 coats)	0,8 m ²

Packaging

Description	Format	Color	Product Code	EAN Code
Spray can	400 ml	RAL 5015 Matt blue	91310/001	8 027354 913017



NOTES:

[illegible]

Tutti i diritti riservati.

È vietata la riproduzione anche parziale di testi, disegni, illustrazioni e fotografie.
È diritto della Eco Service di modificare, annullare o sostituire i prodotti
contenuti in questo stampato, senza obbligo di preavviso.

All rights reserved.

No parts of texts, illustrations, pictures may be reproduced.
It is a right of Eco Service to modify, cancel or substitute the products
contained in this printed matter, without any obligation of notice.

Reservados todos los derechos.

Está prohibida la reproducción de textos, ilustraciones y fotografías total o parcialmente.
Eco Service se reserva el derecho de modificar, anular o reemplazar los productos
contenidos en este impreso, sin obligación de preaviso.



www.eco-servicesrl.it
www.w8.eco-servicesrl.it

ECO SERVICE SRL

VIALE EUROPA, 1 - ZONA INDUSTRIALE
36053 GAMBELLARA (VI) - ITALY
TEL +39 0444 649269 - FAX +39 0444 441190
email: info@eco-servicesrl.it

IBERICA CHEMICAL ECOSERVICE, S.L.

CAMI RATILS, PARCELA 17, S/N - POL. IND. EL COLOMER
12000 ONDA - CASTELLÓN - SPAIN
TEL +34 964913029 - FAX +34 964090282
email: ventas@ecoserviceiberica.com